



# Genfitt

Knock Road, Kiltimagh, Co Mayo, Ireland.  
T: +353 (0) 94 93 81377 F: +353 (0) 94 93 81615  
E: info@genfitt.ie W: www.genfitt.ie




11/11 Contact your local sales representative for pricing or call the office

# Grease Products

---



# 2011/2012



# Grease

## Universal Grease Gun



- Angled spout, G 1/8in, 150 mm
- Coupler, 4 jaws G 1/8in
- Greases up to NLGI grade 2
- Acc. to DIN 1283
- Wall thickness of grease gun tube: 1.0 mm
- Colour: silver

**G1390**

## Professional Grease Gun



- Angled spout , M 10 x 1, 150 mm
- Precision machined coupler, 4 jaws, M 10 x 1
- Variable Stroke System
- Double Lock
- Greases up to NLGI grade 2
- Designed to be utilised under rough conditions
- Acc. to DIN 1283
- Wall thickness of grease gun tube: 1.5 mm
- Colour: graphite-grey

**G1392B**

## Grease Gun with Flexible Hose



- High pressure hose, G 1/8in, 8 x 300 mm
- Coupler, 4 jaws G 1/8in
- Greases up to NLGI grade 2
- Acc. to DIN 1283
- Wall thickness of grease gun tube: 1.0 mm
- Colour: silver

**G1392**

### Grease cartridges suitable for these Grease Guns

## EP2 Lithium Grease

- Multi-purpose grease that provides excellent lubrication in both high and low temperature conditions
- Recommended for lubrication of both plain & anti-friction bearings in a wide variety of applications



**G1393** 400g

## Pin and Brush Grease

- Recommended for lubrication of friction and roller bearings under difficult conditions
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability




**G17405** 400g

## Longlife Red EP2 Grease

- Recommended for lubrication of both plain & anti-friction bearings in a wide variety of applications
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability



**G17406** 400g



# Grease



## 2 Handle Kajo Grease Gun

- Heavy duty two handed grease gun
- Complete with armoured pipe and nozzle tube
- Suitable for 400g and 500g cartridges
- Colour: silver/blue

**G16692**

## EP2 Standard Grease



- Multi-purpose grease that provides excellent lubrication in both high and low temperature conditions
- Recommended for lubrication of both plain & anti-friction bearings in a wide variety of applications
- Lithium
- Optional performance additives: EP2

**G16693** 500g

## LZR 2 Long Duration Grease



- Recommended for lubrication of friction and roller bearings in high load operating conditions
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability
- EP properties

**G16694** 500g

## MOS 2 Pin And Bush Grease



- Recommended for lubrication of friction and roller bearings under difficult conditions
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability

**G16695** 500g

## Chipping Hammer Grease



- Recommended for lubrication of socket tools and wearing bushes of hydraulic and compressed air hammers
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability

**G16696** 500g

## LC 002 Bearing Grease



- Recommended for lubrication of roller and friction bearings in high thermic load capacity and extreme conditions
- Protects against corrosion
- Water resistance
- Excellent oxidation and mechanical stability

**G16697** 500g

**Grease cartridges suitable for Grease Gun ref. G16692**



# Grease

## Pistol Grip Grease Gun



- Straight spout G 1/8in, 150 mm
- Coupler, 4 jaws G 1/8in
- Greases up to NLGI grade 2
- Acc. to DIN 1283
- Wall thickness of grease gun tube: 1.0 mm
- Colour: silver

**G1419** 500cm

## Automatic Air Grease Gun



- Straight spout M 10 x 1,150 mm
- Precision machined coupler, 4 jaws, M 10 x 1
- Greases up to NLGI grade 2
- Wall thickness of grease gun tube: 1.0 mm
- Colour: graphite-grey

**G1418** 500cm

## Telescopic Push Type Grease Gun



- Volume: 150 ml
- Media: grease
- Material of casing: plastic
- Coupler: universal coupler
- Connection: for hydraulic and ball type grease nipples, DIN 71412, DIN 3402
- Pressure: 20 Bar
- Diameter: 50 mm
- Length: 210 mm
- Weight: 0.09 kg

**G1476**

## Gun Trigger for Auto Greaser



- Angled spout
- 4-jaw coupler, G 1/8in (12 743), precision design, machined and slotted
- Ergonomic contoured safety handgrip
- Operating pressure maximum: 400 Bar
- Operating temperature: +60 °C
- Connection 1: G 1/8in female
- Connection 2: coupler, for hydraulic grease nipples, DIN 71412
- Application range: greases NLGI 2

**G13292**



# Grease

## Air Maintenance Unit



- Complete unit
- Thread and male quick release adapter
- Pressure-reducing valve, with manometer, water separator and lubricator
- Connection 1: G 1/4in a
- Connection 2: to suit male rectus quick release airline connector, type 26
- Nominal width: 7.2 mm
- Maximum operating pressure: 10 Bar
- Working pressure max. (bar): 0.5 up to 10 Bar
- Normal flow rate: 6.3 l/sec (at 10 bar supply pressure, and 6 bar operating pressure)
- Filter unit: 40
- Condensate volume: 0.017
- Temperature range: 0 to 50°C
- Casing material: zinc die cast

**G15270**

## Can of Grease 3kg



- Lithium
- Optional performance additives: EP2
- Suitable for auto greaser units

**G1460**

## Can of Grease 12.5kg



- Lithium
- Optional performance additives: EP2
- Suitable for auto greaser units

**G1461**



# Grease

## High Pressure Midi Grease Pump



- Manual pump for grease supply up to NLGI 2
- Suction tube
- Dust cover, with integral pump fixing bracket, fixing screws and follower plate
- High pressure grease hose, 11 x 1200 mm
- Spout, angled, G 1/8in, 150 mm
- Coupler, 4 jaws, G 1/8in
- Robust carrying handle
- Packed in single carton box
- Delivery rate / stroke: 3.8 cm<sup>3</sup>
- Length suction tube: 370 mm
- Discharge hose: high pressure hose, 11 x 1200 mm
- Grease supply: manually lever operated
- Follower plate: for 15 kg container
- Ø follower plate: 240 mm up to 270 mm
- Discharge pressure (bar): 200 bar
- Surface treatment: all steel components are galvanized
- Pump body: steel
- Pump head: impact-resistant zinc die casting
- Lacquering dust cover
- Dimensions: 670 x 420 x 100 mm
- Weight (including package): 4.9 kg

**G1415** High Pressure Midi Greaser

## Low Pressure Midi Grease Pump



- Suitable for grease supply up to NLGI 2
- Filling nipple, M 10 x 1, enclosed without package, for upgrading grease guns from other manufacturers
- Dust cap on filling coupler secured by chain
- Grease gun
- Packed in single carton box
- Length suction tube: 510 mm
- Connection discharge side: for grease guns, with filling nipple
- Discharge: by means of a hand pump
- Follower plate: for 15 kg container
- Diameter: follower plate: 240 mm up to 270 mm
- Delivery rate / stroke: 30 cm<sup>3</sup>
- Grease supply: 8 Bar
- Application: for filling lever, one hand and air operated grease guns
- Surface treatment: all steel components are galvanized
- Pump head: impact-resistant zinc die casting
- Pump body: steel
- Dimensions packaging: 670 x 420 x 100 mm
- Weight (including package): 5.6 kg

**G1416** Low Pressure Midi Greaser



# Grease

## 15kg Air Bucket Greaser



- Suitable for grease supply up to NLGI 2
- High pressure grease hose, 11 x 1200 mm
- Spout, angled, G 1/8in, 150 mm
- Coupler, 4 jaws, G 1/8in
- Robust carrying handle
- Supplied with trolley
- Delivery rate / stroke: 3.8 cm<sup>3</sup>
- Length suction tube: 370 mm
- Discharge hose: high pressure hose, 11 x 1200 mm
- Grease supply: air operated
- Follower plate: for 15 kg container
- Diameter follower plate: 240 mm up to 270mm
- Discharge pressure: 200 Bar
- Surface treatment: all steel components are galvanized
- Pump body: steel
- Pump head: zinc die casting
- Dimensions: 200 x 350 x 1004 mm
- Weight (including package): 4.9 kg

**G1417** Air Bucket Greaser 15kg

## 50kg Air Bucket Greaser



- Suitable for grease supply up to NLGI 2
- Air pump for grease supply
- Suction tube
- Dust cover, with integral pump fixing bracket, fixing screws and follower plate
- High pressure grease hose, 11 x 1200 mm
- Spout, angled, G 1/8in, 150 mm
- Coupler, 4 jaws, G 1/8in
- Robust carrying handle
- Length suction tube: 680 mm
- Connection discharge side: for grease guns, with filling nipple
- Discharge: air
- Follower plate: for 50 kg container
- Diameter follower plate: 335 up to 385 mm
- Delivery rate / stroke: 30 cm<sup>3</sup>
- Grease supply: 8 Bar
- Application: for filling lever, one hand and air operated grease guns
- Surface treatment: all steel components are galvanized
- Pump head: zinc die casting
- Pump body: steel
- Dimensions packaging: 800 x 420 x 100 mm
- Weight (including package): 6.5 kg

**G13365** Air Bucket Greaser 50kg



# Grease

## Portable Oil Dispensing Unit



- Suitable for oils, up to SAE 40, self-lubricating, non-aggressive fluids
- Discharge hose, 2000 mm, with steel discharge spout
- Lacquering, oil-resistant
- Portable, with robust handle
- Suction tube, with pump
- Container cover, with drip opening
- Delivery rate / stroke: 85 cm<sup>3</sup>
- Oil delivery: utilizing a hand pump
- Container capacity: 12L
- Container diameter: 185 mm
- Container height: 380 mm
- Filling: manual, utilizing a removable pump
- Discharge: through discharge hose and steel discharge spout
- Surface treatment: all steel components are galvanized
- Pump head: impact-resistant zinc die casting
- Lacquering container and cover
- Dimensions: 480 x 200 x 600 mm
- Weight: 5.2 kg

**G1420A** Bucket Oil Transfer (Metal)

## Filling System With Connecting Coupler



- Suitable for grease supply up to NLGI 2
- Dust cover, stabilising-fixing bracket and follower plate
- Grease supply hose with female quick release adapter
- Packed in single carton box
- Length suction tube: 510 mm
- Connection suction side: rectus coupling, type 72, for male quick connecting adapter
- Hose length: 1500 mm
- Grease supply: manually lever operated
- Delivery rate / stroke: 30 cm<sup>3</sup>
- Discharge pressure: 8 Bar
- Follower plate: for 15 kg container
- Diameter follower plate: 240 mm up to 270 mm
- Application: for filling centralized lubrication systems
- Surface treatment: all steel components are galvanized
- Pump head: impact-resistant zinc die casting
- Pump body: steel
- Dimensions packaging: 670 x 420 x 100 mm
- Weight including package: 4.8 kg

**G13763** Bulk Greaser 15kgs 17012